

Wireless presentation system for standard meeting rooms



ClickShare makes connecting to the meeting room's video system a matter of clicking a button. This one click wonder not only helps the presenter get the presentation on-screen in a second, but it also allows the other people in the meeting to participate more actively. This is done using the unique ClickShare Button, or by installing a simple app to share content from an Android or iOS smartphone or tablet. The result is enhanced meeting efficiency and better decision-making.

Instantly on screen, using any device

A ClickShare CSM-1 set consists of two USB-powered devices (the 'ClickShare Buttons') and a Base Unit. The Base Unit has a fixed connection to the meeting room's visualization system, and takes care of all the needed processing. Users who want to get their presentation on the large meeting room screen, simply connect a Button to their PC or MAC. They start the application, click the ClickShare Button and immediately their desktop is wirelessly transferred to the large visualization system. Alternatively, when using a smartphone or tablet (either iOS or Android-powered), a simple app allows you to share content as well.

A new meeting dynamic

ClickShare changes the way you meet. Instead of focusing on one presenter, ClickShare encourages all attendees to participate. By showing visual content on the large meeting room screen, it becomes easier for everybody to prove their point. The system's stability and ease-of-use, also drastically limits the number of needed interventions by the IT department.

Specifiche tecniche

CSM-1

Specifiche generali	
Sistema operativo	Windows XP/Vista/7/8 32 & 64 bit Mac OSX 10.6/10.7/10.8 Android 2.2 and later (ClickShare mobile app) iOS 5.0 and later (ClickShare mobile app)
Uscite video	HDMI (video and audio)15-pin VGA
Velocità fotogrammi	Up to 30 fps depending on environment
Risoluzione uscita	HDMI: 1280x720 (720P), 1920x1080 (1080i/1080p) VGA: (SVGA (800x600) / XGA (1024x768) / WXGA(1280x768) / WXGA+(1280x800) / 1360 * 768 / 1440 * 900 / 1600 * 1200
Risoluzioni ingresso	Up to 2048x1536 (QXGA)
Numero di risorse contemporanee visualizzate	1
Numero di connessioni contemporanee	8
Audio	Radio quality 16bits 22KHz (no synchronization) via audio jack or HDMI
compatibilità iPad e iPhone	Available via ClickShare app for static content.
Protocollo di autenticazione	WPA2-PSK
Protocollo di trasmissione wireless	IEEE 802.11 a/b/g/n
Data rate wireless	Up to 300Mbps
Portata	Max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit, depending on environment
Banda	2.4 GHZ and 5 GHz
Alimentazione	External Power adaptor 5V DC input 2.6A (included in set)
Connessioni	USB Host x 2 RJ-45 LAN Port Audio analog line out on mini jack socket (3.5mm)
Intervallo di temperature	Operating: 0°C to +40°C (+32°F to +104°F) Storage: -10°C to +60°C (+14°F to +140°F)
Umidità	Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 80% relative humidity, non-condensing
Montaggio a parete	Included in set
Certificazioni	FCC/CE
Garanzia	3 years standard
Dimensioni dell'unità di base ClickShare	
Dimensioni (AxLxP)	Excl. antennas: 37mm x 186mm x 85mm / 1.457" x 7.323" x 3.346" Incl. antennas: 125mm x 186mm x 121mm x / 4.921" x 7.323" x 4.763"
Peso	530g / 1.17lbs (incl. antennas)

Generato il: 05 dic 2013
Le informazioni e i dati forniti riguardano l'apparecchiatura descritta.
Tuttavia ogni singolo articolo è soggetto a modifiche senza preavviso.
L'ultima versione di questo opuscolo è disponibile all'indirizzo
www.barco.com.

BARCO

Visibly yours