

# Business-Class Video Conferencing for the Small Meeting Room



## Lifesize® Icon Flex™



## It's Your Meeting—You Choose the Application

At Lifesize, we know there's a better way to have an exceptional meeting experience because we've spent over a decade perfecting it. Meet Lifesize Icon Flex—a complete, business-class video and audio conferencing solution ideally suited for small meeting rooms that gives businesses the power of choice. So whether your business is using Microsoft® Lync®, Google Hangouts™, Cisco Jabber®, Skype™, or our favorite, Lifesize® Cloud, all you have to do is bring your laptop to the meeting and connect it to Lifesize Icon Flex for a video collaboration experience like no other.

And what makes Lifesize Icon Flex stand out from the rest is that our elegantly designed Lifesize Phone can also be used as a stand-alone conference phone, giving your company one less device to manage in the meeting room.

Best of all, Lifesize stands by every solution we make with our world-class service and support team.

Your laptop. Your collaboration app. Lifesize Icon Flex. It's that simple.



## Your Meeting, Your Way

- Perfectly sized for small meeting rooms
- Designed for use with collaboration applications like Microsoft Lync, Google Hangouts, Cisco Jabber, Skype (or our favorite, Lifesize Cloud)
- Business-class, award-winning hardware provides an exceptional meeting experience
- Backed by our world-class customer service and support team that's always there when you need them

### LIFESIZE CAMERA

- Provides superb, lifelike HD 1080p30/720p60 video
- Ultra-quiet pan/tilt with 6x zoom: 3x optical zoom and 2x digital zoom
- Low-dispersion, 8-element glass lens, with anti-glare coating and high clarity, molded aspherical glass
- Proprietary lens iris reduces optical diffraction
- Razor-sharp image quality provided by five-zone autofocus
- Increased durability and optimal heat distribution through machined aluminum body

### LIFESIZE PHONE

- Elegantly designed touchscreen conference phone with 360° microphone coverage and powerful loudspeaker for maximum voice pickup and crystal-clear audio
- Can be used as a stand-alone audio conference phone by connecting to your IP-PBX

### LIFESIZE REMOTE CONTROL

- Controls camera (pan/tilt/zoom) and audio (mute/volume)

## SYSTEM COMPONENTS

Lifesize Icon Flex with embedded PTZ camera  
Lifesize Phone or Lifesize Digital MicPod  
Lifesize Remote Control  
Power supply and cable (2 m)  
USB A to USB B cable (5 m)  
HDMI cable (5 m)  
Ethernet cable (3 m)  
Quick reference card

## SYSTEM REQUIREMENTS

Windows 7 or higher  
Mac OS X 10.8 or higher  
USB 2.0 port

## DESIGNED FOR USE WITH:

Microsoft Lync  
Google Hangouts  
Cisco Jabber  
Skype  
Lifesize Cloud  
Windows®  
Mac®

## TECHNICAL SPECIFICATIONS

1080p30 6x PTZ camera  
– Full HD 1920x1080p30/1280x720p60 resolution  
– Progressive scanning  
– 16:9 aspect ratio  
– Wide-angle zoom lens with 70-degree field of view  
– 245-degree pan, 72-degree tilt  
– 3x optical lossless zoom  
– 2x digital zoom  
– Power LED

## VIDEO OUTPUT (1)

1 x USB B (1080p30/720p60) to laptop  
Laptop can be connected to HD display separately

## FULLY INTEGRATED, HD AUDIO LIFESIZE PHONE

90 Hz up to 22 kHz  
32 kHz audio sampling  
Pickup range up to 4.57 m (15 ft)  
Powered by Lifesize Icon Flex through Lifesize Link cable  
Ships with 9 m Lifesize Link cable  
Optional 4 m or 15 m cable available

System Speaker  
– Powerful rare-earth magnet loudspeaker driver  
– Large, acoustically suspended speaker enclosure

System Microphones  
– Four low-noise microphones  
– 80 dB SNR before noise reduction  
– Sample rates: 32 kHz  
– Beam-forming algorithm steers the microphones to the location of the talker for greater voice pickup and reduced room noise

Touchscreen Display  
– WQVGA capacitive multitouch display  
– 4.3 inch (diagonal)

## FULLY INTEGRATED, HD AUDIO LIFESIZE DIGITAL MICPOD

90 Hz up to 22 kHz  
Sample rates: 32 kHz  
Pickup range up to 4.57 m (15 ft)  
Powered by Lifesize Icon Flex through Lifesize Link cable  
Ships with 4 m Lifesize Link cable  
Optional 9 m or 15 m cable available

System Microphones  
– Three low-noise microphones  
– 80 dB SNR before noise reduction

## GENERAL AUDIO FEATURES

Full duplex for natural conversations  
Echo cancellation for echo-free calls  
Automatic gain control  
Automatic noise reduction

## AUDIO INPUT (1)

1 x Lifesize Link (Lifesize Phone/Digital MicPod) via USB cable to laptop

## AUDIO OUTPUT (1)

1 x Lifesize Link (Lifesize Phone) via USB cable to laptop

## USER FEATURES

Heads-up remote control  
Intelligent touchscreen interface with Lifesize Phone  
Manage camera pan, tilt, zoom, audio mute/unmute, volume up/down  
LEDs on phone or micpod for in-call (blue) and mute (red) indication

## SECURITY

Kensington Security Slot

## POWER

AC voltage 100–240V, 50–60 Hz, 2.31A via external 19VDC power supply

## ENVIRONMENTAL DATA

Operating temperature: 0°C (32°F) to 40°C (104°F)  
Operating humidity: 15% to 85%, noncondensing  
Storage temperature: –20°C (–4°F) to 60°C (140°F)  
Storage humidity: 10% to 90%, noncondensing

## DIMENSIONS

Width: 216.5 mm (8.52")  
Depth: 119.4 mm (4.70")  
Height: 125.4 mm (4.94")  
Weight: 1.04 kg (2.29 lbs)

## MOUNTING OPTIONS

Mounting holes: 2 x M5 screw holes 150 mm (6 in) apart  
Mounting screws: 2 x M5 screws (Max insertion depth: 3.8 mm)

## REGULATORY NUMBER:

LFZ-033

## RUNS ON:



## DESIGNED FOR USE WITH:



Performance dependent on collaboration application being used.

## HEADQUARTERS

Austin, Texas, USA  
+1 512 347 9300  
Toll Free US +1 877 543 3749

## APAC REGIONAL OFFICE

Singapore  
+65 6303 8370



www.lifesize.com  
E-mail: info@lifesize.com

# lifesize

## EMEA REGIONAL OFFICE

Munich, Germany  
+49 89 20 70 76 0  
Toll Free Europe +00 8000 999 09 799

© 2015 Lifesize, a division of Logitech. All rights reserved. Information contained in this document is subject to change without notice. Lifesize is the registered trademark or trademark of Logitech. All other trademarks are the property of their respective owners.

DS\_IconFlex\_EN\_0115