

Accessories













XP-6

Control Processor

The XP-6 is the powerful centerpiece of any professionally installed control system, designed to automate and enhance the operation of A/V, security, lighting, HVAC, and countless other devices in a commercial or residential environment. The XP-6 is packed with features to facilitate integration of third-party devices into one seamless and cohesive system, with a variety of communication options such as RS-232, relay, IP, and routable IR control. Additional RTI accessories can be incorporated to allow wireless communication between an RTI remote control and the XP-6, even through walls or cabinets. The processor features built-in support for the RTI 433-MHz receivers for one-way RF communication, or powerful ZigBee® 2.4-GHz transceivers can be incorporated for more sophisticated bidirectional communication between the RTI controller and central processor and supported devices.

Key Features

- Powerful 32bit, 533MHz CPU.
- 128Mb of non-volatile Flash memory.
- Six multi-purpose I/O ports.
- Three programmable 12VDC trigger outputs.
- Three assignable voltage sense inputs.
- · Three programmable relay outputs.
- Two RS-232 ports for bi-directional communication.
- Built-in astronomical clock for time-based events and sleep timers.
- Compatible with all RTI wireless remote controls (when used with RTI RF antennas/Zigbee® transceivers) and In-wall controllers.
- Multi-purpose I/O ports are compatible with industry standard IR emitters, blasters, and repeater systems.
- Input for connection of multiple RF receiver modules.
- Variable IR output on all ports.
- Multi-purpose I/O ports support all optional RTI power sensing and communications modules.
- Programmed using the Integration Designer® Software.
- Non-volatile Flash memory stores your system configuration even when power is not present.
- Fast USB 2.0 and Ethernet programming.
- Field upgradable firmware.



Specifications

Power Supply+12V DC, 1A		
IR Output Ports		
IR Output Drive		
Infrared Frequency Transmission Range		
Infrared Input		
Trigger OutputsThree, 12 VDC, 100mA max each		
RelaysThree, 3 Amps @ 30 VDC		
Sense Inputs		
RS-232 PortsTwo, Bi-directional RJ45 Connections		
Ethernet Port		
USB Ports One, Programming		
RTI Com PortZigbee® Communication Port, RJ45 Connection		
Mounting		
Dimensions (W x H x D) 10.3" (262mm) x 5.25" (134mm) x 1.5" (38mm)		
Weight		
WarrantyOne Year (Parts & Labor)		
All specifications subject to change without notice		



XP-6 Control Processor

RTI User Interfaces

RTiPanel	Mobile Software Interface (App)
Virtual Panel	PC Software Interface (App)
SURFIR	Companion Remote Control
T1-B+	Remote Control
T2i	Remote Control
T2x	Remote Control
T3x	Remote Control
RKM-1+	In-Wall Audio Distribution Keypad
RK1+	2-4-8 Button In-Wall Keypad
KX2	2.8 inch In-Wall Touchpanel Keypad
КХ3	3.5 inch In-Wall Touchpanel Keypad
KX7	7 inch In-Wall Touchpanel
CX7	Countertop/Under-Cabinet Touchpanel







RTI Control Accessories

RP-4	RF Control Processor
XP-3	Advanced Control Processor
XP-6	Advanced Control Processor
XP-8s	Advanced Control Processor
RM433	433MHz RF Antenna
ZM24	2.4GHz Zigbee Transceiver
CB-8	Touchpanel Connecting Block
CM-232	RS-232 Communication Module
CPB-1	Control Port Connecting Block
ECB-5	IR Connecting Block
ESC-2	Ethernet to Serial Converter
IPE-4	IR Port Expander
PCM-4	Port Control Module
RCM-4	Relay Control Module
IRsa Mouse	IR Emitter



RTI Audio Distribution

AD-4x Distributed Audio System
AD-8x Distributed Audio System
CP-450 4 Channel Amplifier
CP-1650 16 Channel Amplifier



5775 12th Avenue East, Suite 180, Shakopee, MN 55379 PH: (952) 253-3100 • Website: www.rticorp.com

