



# CS-700



## Video Sound Collaboration System for Huddle Rooms

The Yamaha CS-700 video sound collaboration system is specifically designed as an all-in-one unit to equip huddle rooms with best in class audio, video, and screen sharing capability. Huddle rooms have unique requirements, as they typically are small sized rooms with limited tabletop space. The Yamaha CS-700 combines ultra-wideband audio with high-quality video to fulfill video, audio, and collaboration requirements in one simple, wall-mounted system addressing all communication and collaboration requirements of the huddle room. Audio, video and screen sharing is accomplished through one USB cable. The integrated remote management capability enables IT departments across the world to remotely monitor and manage their huddle room installations.

### Video

Due to the small size of huddle rooms, participants sit close to displays and cameras in these rooms, in the past requiring panning of video cameras to see the whole room. The Yamaha CS-700 industry-leading 120 degree ultra-wide angle camera captures all meeting participants in one field of view. The CS-700 camera covers 80% more area in the whole room, removing the hassle of panning and zooming cameras to see



everybody in the room. The high pixel count of the CS-700 ensures that every expression is captured and seen for people up to 10ft/3m from the camera. It is truly a “set it and forget it” video system.

### Audio

“Hear every word” has never meant more to meeting success than today. The CS-700 takes advantage of years of professional and corporate audio experience within

Yamaha and Revolabs. The CS-700 features a beamforming microphone array that picks up every word spoken in the room and delivers it to the far end. A four-element speaker bar provides amazing audio in the room, ensuring that every word spoken at the far end is heard. Combine that with award-winning audio processing technology integrated in the CS-700 and you have easy, natural conversations between meeting participants with clarity and intelligibility for all.

### USB, Bluetooth® and SIP support

The Yamaha CS-700 becomes the one communication device in the room. It supports business communication applications such as Microsoft® Skype for Business™, Google Chromebox for Meetings™, BlueJeans®, Zoom®, GoToConference™, Vidyo® and others. In addition, the CS-700 provides a SIP interface to the corporate call manager, replacing the need for a separate conference phone in the huddle room. USB and SIP communications can be easily bridged in the CS-700, expanding the communication opportunities even further. And Bluetooth allows for fast and easy audio connections, instantly turning a mobile or computer call into a conference call.

### Wall mount

Table space in huddle rooms is typically at a premium. The Yamaha CS-700 is a wall mount system, eliminating any need for table-top equipment in the huddle room.

The wall mount provides simple installation and makes connecting the wires to the CS-700 easy by use of a special pivot design feature. If you can drill a hole, you can install the CS-700.



### Remote Manageability

Managing up to hundreds of huddle rooms is a challenge for any IT department. The Yamaha CS-700 enables remote monitoring and management of the units as ►

well as configuring units in bulk. Upgrade them remotely and automatically through the IP interface. Managing technology in the huddle room just became way simpler!

### Collaboration

The Yamaha CS-700 supports DisplayLink™ to provide best collaboration support in the huddle room. This allows sharing of up to two screen contents on displays in the room using the same USB connection for video and audio, reducing the clutter and cables required on the huddle room table.


### Available versions

- CS-700AV:** Audio, Video, IT management
- CS-700DL:** Audio, Video, IT management, DisplayLink™
- CS-700SP:** Audio, Video, IT management, SIP interface
- CS-700DS:** Audio, Video, IT management, DisplayLink™, SIP

## MAIN FEATURES

- **USB audio and video support for UC applications**
- **Beam forming microphone array**
- **4 speaker element sound bar**
- **Ultra-wide angle camera with 120 degree field of view**
- **Integrated SIP interface for Call Manager integration**
- **DisplayLink™ interface**
- **Remote Administration and Management, System notifications (SNMP), Auto configuration support**

## TECHNICAL SPECIFICATIONS

<b>AUDIO</b>  Speaker Bar  Speaker Frequency Response Max SPL Microphones Microphone Coverage Microphone Frequency Response Full Duplex Audio Echo Cancellation LED indicator	4 Speaker elements with tweeter and mid-Woofer on left and right 160 – 20,000 Hz 90 dB at 1 M 4 microphone beamforming array 180 degrees audio pickup 160 – 16,000 Hz Yes Ultra wideband AEC Mute/unmute	<b>COMPLIANCE</b>  Safety  EMC  Environmental	IEC60065, IEC60950, IEC62368 CISPR13/CISPR22/CISPR32/ FCC/J55013/ ETSI EN 300 328 / ETSI EN 302 291-2 / ETSI EN 300 330-2 EN55024/ CISPR24 or 35 and ETSI EN 301 489-1 RoHS, Reach, WEEE
<b>INTERFACES</b>  Mount  Connector USB Host Port Ethernet Bluetooth® Aux Audio Input	Wall Mount Bracket for above or below display mounting USB with strain relief Audio, video, HID and graphics display supported over USB 3.0 RJ 45 Audio only 3.5mm Stereo	<b>WARRANTY</b>  Global except for EU European Union	1 Year return to factory 2 Year return to factory
<b>CAMERA</b>  Camera Sensor Privacy Cover LED Indicators UVC Support Field of View	High Definition CMOS Manual privacy cover Camera Operational LED UVC 1.5 120 degrees	<b>SIZE, WEIGHT, POWER</b>  Height Length Width Weight (incl. bracket) Input Voltage Input Current Input Frequency Power Consumption Power Cord Length	3.9in/98.75mm 2.7in/68.5mm 34.in/861.7mm 7.3 lbs/3.3kg 100-240 VAC 1A 50-60 Hz 36W 10ft/3m - Please order correct SKU for regional power cord requirements
<b>SIP</b>  Call Handling  Call Bridging  Codecs DTMF Support Security  Network & Provisioning	Make, Answer, Hold, Resume, Transfer (Blind and Supervised), Forwarding, Do not disturb, Redial, Call Timer, Call ID, Speed Dial, Missed Call Notifications, Voice Mail Notifications (switch configured) Supports Bridging SIP and USB Calls. Join, Split, Hold, Resume, 3+1 Lines: Up to 2 SIP calls, 1 USB call, plus the user G.711 (A-law and μ-law), G.722, G.726, G.729 RTP event, SIP in-band, SIP info package SRTP/SRTCP Support (RFC 1889), IETF SIP support (RFC 3261 and companion RFCs), SSIP, Password protected configuration files, Password protected login DHCP or Static IP, Server Based Central Provisioning, Web Portal for Individual Unit Configuration	<b>AVAILABLE FROM</b>	<div style="text-align: center;">                   Revolabs, Inc.                  144 North Rd, Suite 3250                  Sudbury, MA 01776                  United States of America                  Phone: +1-978-610-4040  <b>Email: sales@revolabs.com</b>  <b>Web: revolabs.com</b> </div>
			YAMAHA CORPORATION P. O. Box 1, Hamamatsu, Japan <a href="http://www.yamaha.com/products/en/communication/">http://www.yamaha.com/products/en/communication/</a>